

INTRODUCING RELS X SERIES

RELS 1250X TIRE CHANGER

Semi-Automatic Swing-Arm Machine

BEADBREAKER FOR 16" WHEELS
QUICKCHANGE DUCKHEAD IS STANDARD
REPLACEABLE INSERTS PROTECT ALUMINUM WHEELS
PLASTIC AND METAL DUCKHEADS ARE STANDARD
NON METALIC JAW COVERS ARE STANDARD
AIR JETS ON EVERY CLAMP
STORAGE FOR TOOLS
LUB BUCKET HOLDER
HANDLES A 50" TIRE & WHEEL
TECHNICAL DATA

BEAD BREAKER FORCE	5,510 LBS.
MOTOR	1 HP, 110VAC, 1PH
MAXIMUM TIRE DIAMETER	50"
TIRE WIDTH	3" TO 16"
INSIDE CLAMPING CAPACITY	14" TO 24"
OUTSIDE CLAMPING CAPACITY	13" TO 22"
CLAMPING CAPACITY	
IS ACCURATE ON MOST WHEELS	



Quick change duckhead with both metal and plastic duckhead is standard on all Models



RELS MANUFACTURING

414-727-1770 Fax 414-727-1772 (800)432-7357 www.relsmfg.com