

INTRODUCING RELS X SERIES

RELS 802X WHEEL BALANCER

Automatic Distance & Diameter Measurement

HOOD IS STANDARD
MEASURES IN GRAMS OR OUNCES
EASY SELF CALIBRATION
SOLID STEEL BODY
AUTOMATIC DISTANCE MEASUREMENT
STATIC BALANCE
ELEVEN BALANCE MODES
THREE ALU SETTINGS
AUTOMATIC DIAMETER MEASUREMENT
FOUR CONE SETS
QUICK NUT IS STANDARD

MAXIMUM TIRE 7 WHEEL DIAM.: 44"
RIM DIAMETER: 10" TO 24"
RIM WIDTH: 1.5" TO 20"
ACCURACY: + OR - 1 GRAM
220/115V 1 HP



802X ACCESSORY PACK KIT

A #72099 Caliper
B #72001 Quick Lock Nut
C #72002 Protection Cup
D #12440 Centering cone 1.75" x 2.625" (44.44 x 66.675mm)
E #12540 Centering cone 2.562" x 3.50" (68.09 x 88.90mm)
F #12640 Centering cone 3.375" x 4.3125" (85.72 x 109.54mm)
G #12740 Centering cone 4.25" x 5.125" (107.95 x 130.18mm)
H #44048 Spring
I #44045 Calibration Weight
J #72098 Wheel Weight Pliers



Optional Motorcycle adapter

RELS MANUFACTURING

414-727-1770 Fax 414-727-1772 (800)432-7357 www.brakelathes.net